

Fácil Line

Quick installation,
multiple usages.



fácil

**Quick installation,
multiple usages.**



ADVANTAGES

Absolute privacy in your calls

You can forward calls, talk and query among extensions.

Cheaper telephone bill: blockage of mobile calls and long distance calls.

Door phone: you can answer and open the door from any phone within the house.

Ready for Internet: it warranties a quicker and safer navigation.

Pre-programmed for easy use.

EQUIPMENT

Fácil 1.4: single equipment 1x4

Fácil 3.8: base equipment 2x8

Growth: 3x8

ACCESORIES

CO line board.

Standard door phone board (4 wires).

Door phone board (2 wires).

TECHNICAL SPECIFICATIONS

Power supply

220 VCA +/- 10%, 50 Hz, 15 W.

Internal lines

Use of standard tone / pulse telephones.

Maximum wiring distance, a pair 1800 m (AWG22 wire).

CO lines

Connection to public or private PBXs (15-100 mA, 24-60 VCC), either by tones or pulses.

Surge and transient protection, with the most updated semi-conductors.

RJ11 connector for all CO lines.

General specifications

Automatic WATCH DOG reset system.

Total program maintenance in case of power shortage.

Working temperature: 32°F to 104°F.

Wall mounted.

Dimensions (mm): 205 (width) x 270 (height) x 65 (length).

Weight: 1,8 Kg.

MOST OUTSTANDING FUNCTIONS

- Access to programmable CO line.
- Blockage of local, national, international, mobile phone, audiotext and free phone calls.
- Programmable flash time.
- Speedy internet.
- Music on hold.
- Conference between one CO line and two extensions.
- Door phone bell in extensions (**Accesory:** Door phone).
- Day/night service.
- Directed hunt.
- General hunt.
- Call holding.
- Call parking.
- Forwarding with query.
- Query.
- Last number recall when forwarding is not answered.
- Switch between CO and internal line.
- Recall from parking line.
- Dial reopening.
- CO line flash.
- General CO line access.
- Directed CO line access.
- Automatic callback from busy CO line.
- Automatic callback from busy extension.
- Call forwarding.
- Do-not-disturb function.



JUST INTALL IT

Approved by
CNC Regulation
SC-ST2-45.02

