


## Nexo Selenia 8.24

Maximum capabilities,  
higher performance.



Selenia  
8.24

**NEXO**<sup>®</sup>  
nos comunica mejor



## Maximum capabilities, higher performance.

### ❖ ADVANTAGES

A large variety of usages, a major capacity and the versatility in adding accessories to increase its functions are combined to offer you this distinguished PBX, an excellent instrument for the growth of your company.

### ❖ EQUIPMENT

**Selenia 8.24:** base equipment 4x12  
Growths: 4x14 - 4x16 - 4x18 - 4x20 - 4x22 - 4x24  
5x... - 6x... - 7x... - 8x...

### ❖ ACCESSORIES

2 extension board.  
2 key system extension board.  
2 Caller ID extension board.  
1 CO line board.  
4 Caller ID in LU board.  
Standard door phone board (4 wires).  
Door phone/Pager board (4 wires).  
Door phone board (2 wires).  
Door phone/Pager board (2 wires).  
Automated attendant-DISA-Fax board  
LAN Board + RS232 Port.  
2nd port RS232 board.  
8 I/O module.

### ❖ TECHNICAL SPECIFICATIONS

#### Power Supply

220 VCA +/- 10%, 50 Hz, 20 W.

#### Internal Lines

Use of standard tone / pulse telephones and 4-wire key system telephones.  
Maximum wiring distance, a pair 1800 m (AWG22 wire).  
Extensions.  
Connection through auto-pressure connectors.

#### CO Lines

Connection to public or private PBXs (15 a 100 mA, 24 a 60 VCC), either by tones or pulses.  
Surge and transient protection, with the most updated semi-conductors.  
RJ11 connector.

#### General Specifications

Automatic WATCH DOG reset system.  
Total program maintenance in case of power shortage.  
Working temperature: 32°F to 104°F.  
Wall mounted.  
Dimensions (mm): 530 (width) x 330 (height) x 85 (length).  
Weight: 6,5 Kg

### ❖ FUNCIONES MAS DESTACADAS

- Up to two door phone fronts answering. (Accessory: Door phone + Door phone/Pager).
- Holds 2 automated attendant-DISA-Fax board.
- Caller ID. (Accessory: 4 Caller ID in LU board+ 2 key system extension board/2 Caller ID extension board).
- LAN connection. (Accessory: LAN board + RS232 port).
- Holds 2 RS232 ports. (Accessory: 2nd RS232 port board).
- Holds 8 inputs and outputs for actions over other equipments. (Accessory: 8 I/O module).
- Music on hold.
- Dial Up speedy internet.
- Automatic phone call routing.
- Flexible numbering for extensions.
- Wide block menu.
- Chart of allowed or not admitted numbers.
- Individual phonebook with 49 positions, general with 50.
- CO line time.
- Tele-program. (Accessory: Automated attendant-DISA-Fax).
- PC programming.
- Key system telephone operation. (Accessory: 2 key system extension board).
- DSS console operation. (Accessory: 2 key system extension board).
- PC operation console. (Accessory: LAN board + RS232 port).
- Automated attendant of external calls. (Accessory: Automated attendant-DISA-Fax).
- Direct Inward Dialing through menu or through extension. (DISA). (Accessory: Automated attendant-DISA-Fax).
- Switch-Fax to programmable extensions. (Accessory: Automated attendant-DISA-Fax).
- Centrex/S.G.P. service accepted.
- Report of incoming and outgoing calls.
- Day/night service.
- Program copy between extensions.
- Phone calls and call hunting according to extension groups.
- Grouped CO lines.
- Programmable flash time.
- Codes of virtual and floating extensions.
- Access codes.
- Do-not-disturb function.
- Conference between one CO line and two extensions.
- Conference between two CO lines and one extension.
- Door phone bell in extensions. (Accessory: Door phone).
- Ding-Dong pager. (Accessory: Door phone/Pager).
- Alarm/Alarm clock.
- Intelligent redial.
- Hot-Line services.
- Alternation.
- Extension lock.

